



CD-V - High Value Capacitive Discharge Welder

The CD-V series welders are high value, compact capacitive discharge welders featuring dual pulse output with full control of both pulses.

Key Features CD-V - High Value Capacitive Discharge Welder

- > Fully controllable dual pulse output
- > Adjustable pulse separation for process optimization
- > Rapid fire between pulses for quick welding of adjacent location
- > Ultrafast rise time for conductive material welding
- > Pulse rise time control
- > Peak current monitor indicates if weld occurred
- > Programmable squeeze time
- > Weld counter
- > CE compliant
- > Built in the USA

Specifications CD-V - High Value Capacitive Discharge Welder

Modell	CD-V1210A	CD-V1220A
Max. energy output	120 Ws	260 Ws
Weld speed @ 50% (per min)	105	78
Weld functions	Single pulse, dual pulse and roll spot	Single pulse, dual pulse and roll spot
Upslope	Adjustable (between 0.1 and 15 ms)	Adjustable (between 0.1 and 15 ms)
Pulse length	I _{peak} *	I _{peak} *
Programmable squeeze	Yes (0-250 ms, default 100 ms)	Yes (0-250 ms, default 100 ms)
Haltezeit	Controlled via footswitch or handpiece	Controlled via footswitch or handpiece
Schweißzähler	Yes	Yes
Schedules	8 internally programmable schedules	8 internally programmable schedules
2-Level foot switch	Optional	Optional
Ausgangsrelais	No	No
Communication**	No external communication	No external communication
Power input	90-240 VAC, 50/60 Hz, 10 A (standard wall plug)	90-240 VAC, 50/60 Hz, 10 A (standard wall plug)
*	Relative indicator to indicate firing. We recommend an external monitor for actual process monitoring.	Relative indicator to indicate firing. We recommend an external monitor for actual process monitoring.
**	For units with external communication, please see our ADP datasheet	For units with external communication, please see our ADP datasheet
Abmessungen (L x B x H)	379 mm x 221 mm x 205 mm (14.92 in x 8.72 in x 8.06 in)	379 mm x 221 mm x 205 mm (14.92 in x 8.72 in x 8.06 in)
Gewicht	10 kg (22 lb)	10 kg (22 lb)


Product applications CD-V - High Value Capacitive Discharge Welder




Battery tab welding



Interconnects



Honeycomb tacking



Fine wire to pad

AMADA[®]

AMADA WELD TECH

OUR TECHNOLOGIES



OUR SALES OFFICES



AMADA WELD TECH GmbH
Lindberghstrasse 1 • DE-82178 Puchheim, Germany
T: +49 (0) 89 83 94 030 • Fax : +49 (0) 89 839403 68
info@amada-weldtech.eu • www.amada-weldtech.eu
ISO 9001 Certified Company

Please contact our worldwide
network here:



follow us on:



All data, images and text are subject to change at any time. AMADA WELD TECH GmbH reserves the right to change, modify, delete and add technical specifications and product details at any time without prior notification. © 2020 AMADA WELD TECH GmbH.

WWW.AMADAWELDTECH.EU