



MM-410A - Portable Weld Checker

MM-410A enables operators to monitor and manage key welding variables that result in changes in weld heat such as current, voltage, time, and force. The compact, handheld unit supports a wide range of resistance welding technologies including AC, DC inverter, AC inverter, transistor and capacitive discharge. It features a simple and intuitive user interface and color touch panel display



Key Features MM-410A - Portable Weld Checker

- Improved accuracy through ISO 17657 compliant toroidal coil
- Easy setup via 5.7" color touch panel
- Seam welding mode – Monitor AC current and voltage or DC voltage for up to 5 minutes
- ISO 17657 – compliant measurement for current – Requires ISO-compliant toroidal coil
- Data storage via on-board flash drive
- Ethernet (TCP/IP), and USB communication
- Multi-language support: English, Spanish, Japanese, Chinese, Korean, German and French

Specifications MM-410A - Portable Weld Checker

Modello	MM-410A
Current range	1×Sensitivity toroidal coil: 0.100-2.000 kA / 0.30-6.00 kA / 1.00-20.00 kA / 3.0-60.0 kA / 10.0-200.0 kA - 10 ×Sensitivity toroidal coil: 0.010-0.200 kA / 0.030-0.600 kA / 0.100-2.000 kA / 0.30-6.00 kA / 01.00- 20.00 kA
Current item	PEAK / RMS* / Arithmetic mean RMS - Accuracy ±1% Full scale
Voltage range	0.30-6.00 V / 1.0-20.0 V - Accuracy ±1% Full scale
Voltage item	PEAK / RMS* / Arithmetic mean RMS
Intervallo forza	4.90-98.06 N (MA-520B), 49.0-980.6N (MA-521B), 245-4903 N (MA-770A), 490-9806 N (MA-522B, MA- 771A)
Force item	Mean RMS/maximum (peak) Before welding / After welding / Constant - Accuracy ±3% Full scale
External input voltage / current range	-10 to +10 V / 4 to 20 mA
External range	±0.5 to 10 V or 4.8 to 20 mA (5% to 100% of rated setting)
External item	Mean RMS/maximum (peak) Before welding / After welding / Constant - Accuracy ±3% Full scale
External units	V / N / kgf / lbf / °C / °F / Mpa / bar / psi
Measurement time current voltage power resistance AC	ms-AC: 1-5000ms
Measurement time current voltage power resistance AC	CYC-AC: 0.5-250.0CYC (50 Hz), 0.5-300.0CYC (60 Hz)
Measurement time current voltage power resistance AC	CYC***Hz-AC: 0.5-200.0CYC (M050: 50 Hz), 0.5-300.0CYC (M063: 63Hz), 0.5-2000.0CYC (M500: 500 Hz)
Measurement time current voltage power resistance AC	LONG CYC-AC: 0.5-500.0CYC (50 Hz), 0.5-600.0CYC (60 Hz)
Measurement time current voltage power resistance DC	CYC-DC: 0.5-100.0CYC (50 Hz), 0.5-120.0CYC (60 Hz)
Measurement time current voltage power resistance DC	ms-DC: 1-2000 ms
Measurement time current voltage power resistance DC	SHORT ms-DC: 0.50-300.00 ms (0.05 ms increment)
Measurement time force external	1 to 10000 ms Accuracy: ±9 degrees
Angolo di conduzione	0-180 degrees
Power supply voltage	Single-phase 100 to 240 V (50/60 Hz) AC adapter output 9 V DC
External data output	USB / Ethernet (Protocol; TCP/IP)
Lingue	Japanese, English, Chinese, Korean, German, French, Spanish
No. of schedules	127 schedules
*	ISO17657 compliant
MASSA E DIMENSIONI	
Dimensions (L x W x H)	47 mm x 224 mm x 157 mm (1.85 in x 8.82 in x 6.18 in)
Massa	Approx. 0.9 kg (1.98 lb)

Drawings MM-410A - Portable Weld Checker



AMADA[®]

AMADA WELD TECH

OUR TECHNOLOGIES



OUR SALES OFFICES



AMADA WELD TECH GmbH
Lindberghstrasse 1 • DE-82178 Puchheim, Germany
T: +49 (0) 89 83 94 030 • Fax : +49 (0) 89 839403 68
info@amada-weldtech.eu • www.amada-weldtech.eu
ISO 9001 Certified Company

Please contact our worldwide
network here:



follow us on:



All data, images and text are subject to change at any time. AMADA WELD TECH GmbH reserves the right to change, modify, delete and add technical specifications and product details at any time without prior notification. © 2020 AMADA WELD TECH GmbH.

WWW.AMADAWELDTECH.EU